

FOLDER DESIGN CHEAT SHEET

IMPORTANT FOLDER TIPS

Every Folder Should:

- ◆ Define who you are.
- ◆ Entice the audience to look inside.
- ◆ Direct the audience to contact information.

Selecting a Product

- ◆ Review stock, coating, and imprint method samples before you order.
- ◆ Choose a heavier stock (at least 100lb or 14pt) for durability.
- ◆ Achieve colorful backgrounds by printing ink on white stock or by allowing your stock color to act as your background.
- ◆ Imprint dark stocks with foil stamping, embossing, debossing, or metallic ink; printing other inks on dark stock can affect color reproduction.
- ◆ Note that die-cut edges will be the stock color, not the ink color.
- ◆ Apply a coating to protect your product, giving it a unique look and feel.
- ◆ Prevent wear and tear with rounded corners, reinforced edges, lamination, or thicker stock.
- ◆ Select expandable or box pockets for carrying more than 30 sheets of copy paper; for up to 30 sheets, choose standard pockets.

Imprint Methods

- ◆ Use PMS (spot) colors to produce designs with just one color (including gradients) or when exact color matching is required.
- ◆ Print four color process (CMYK) for designs with multiple colors.
- ◆ Set black CMYK areas to 60% Cyan, 40% Magenta, 40% Yellow, and 100% Black in your design software for a richer black color.
- ◆ Use 30% more Cyan than Magenta for truest color in blue CMYK areas.
- ◆ Note that metallic or fluorescent colors are not available in CMYK.
- ◆ Emboss or deboss long-fibered textured stocks for a clearer, more pronounced effect.
- ◆ Select fonts more than 1 pt thick for foil stamped text or more than 2 pt thick for embossed/debossed text. Avoid serif fonts or font sizes smaller than 12 pt.

Layout

- ◆ Position artwork so pockets and slits don't obscure your design.
- ◆ Place important logos, text, or other elements on the right 2/3 of the front and back cover to increase their visibility.
- ◆ Leave at least 1/4" space around your logo.

Branding and Legal

- ◆ Match folder colors, design, and messaging to the company's identity.
- ◆ Comply with font and image copyright policies.
- ◆ Include contact information.

Test Printing and Proofing

- ◆ Print a reduced size copy of your design, cut it out, and fold it to check placement of elements.
- ◆ Review your .PDF proof to ensure all details are correct.
- ◆ For four color process designs, request a color digital proof to confirm the color, size and position of elements.

More tips at: www.companyfolders.com/ift

PRINT-READY CHECKLIST

File Setup

- Do NOT delete, modify or move "Template" layer.
- If your product has slits, delete the slits that you DON'T want to appear on the final piece.
- Delete the "Instructions" layer prior to submitting artwork.
- Design in the "Your Art Here" layer of our template.
- Separate each spot coated, foil stamped, embossed, or debossed area into its own labeled, color-coded layer.
- Save file as: **.AI, .EPS, .PDF, .PSD, .INDD, or .TIF.**

Layout

- Avoid placing logos or text near or on die-cut slits.
- Keep important elements within 1/8" safe zone.
- Extend four color process, PMS printed, foil stamped, or spot coated design elements that touch the cut line to 1/8" bleed zone.

Photo Images

- Make raster images 300 DPI at the size they will be printed.
- Embed images, or package them with the primary artwork file.
- Save images as .PSD, .TIF, or .JPG.

Writing

- Proofread all copy for grammar, spelling, and clarity.
- Convert fonts to outlines, or gather fonts using "Package" (Illustrator) or "Collect for Output" (InDesign). Send with art file.
- Include fonts if your final print file is in .PSD format.



Four Color Process

- Set design file and all images to CMYK mode.
- Convert all RGB or spot colors to CMYK.



PMS Printing

- Make sure all graphics are vector format.
- Verify all colors are PMS (spot) colors.



Foil Stamping

- Make sure all graphics are vector format.
- Make elements at least 1pt thick, spaced 1pt or more apart.
- Do not place elements on fold or cut lines.
- Separate each foil color onto its own labeled, color-coded layer.
- Apply a spot color at 100% to represent each foil color. (100% Magenta for first color, 100% Yellow for second, etc.)



Embossing and Debossing

- Make sure all graphics are vector format.
- Make elements at least 2 pt thick, spaced 2 pt or more apart.
- Do not place elements on fold or cut lines.
- Separate each emboss or deboss onto its own labeled, color-coded layer when combining imprint methods.
- Apply a spot color at 100% to represent each emboss or deboss. (100% Magenta for embossed, 100% Yellow for debossed.)

More checklist details at: www.companyfolders.com/prc



COMPANY FOLDERS

Company Folders, the standard bearer of online folder printing, delivers absolute quality infused with the design savvy of an advertising agency.
22 West Huron Street, Suite 203, Pontiac, Michigan 48342 | Tel: 248.738.7600 | Fax: 248.883.8880 | www.companyfolders.com